

[NEWS](#)[THE COMPANY](#)[LIGHTING PRODUCTS](#)[DISTRIBUTOR NETWORK](#)[CUSTOMER SUPPORT](#)[GALLERY](#)[CONTACT US](#)[SITEMAP](#)[HOME](#)

## The 1200 Compact Range

### The 1200 Compact Fresnel



An industry standard 1.0 / 1.2 kW fresnel with a 150mm (6") lens.

The adjustable cone of light has a soft edge, easily blended with adjacent beams to provide even illumination.

Constructed of pressure die-castings and aluminium extrusion, the Compact Fresnel offers efficiency, strength and performance.

### Features

- Wide range of beam angles from 7° to 50°
- High quality industry standard 150mm (6") lens
- Flat even beam with very little spill allows clean masking cut with barndoor flaps
- Yoke balance point adjustable along length of body



- Swing-down door for easy access to re-lamp and clean
- Smooth focus movement given by " Posi-slide" focus system with no metal to metal contact
- Aluminium extrusion and pressure die-casting construction gives strength and style

[Back](#)

[For more information download the .PDF - International version](#)  
(requires [acrobat reader](#)- free download)

[For more information download the .PDF - North American version](#)  
(requires [acrobat reader](#)- free download)

[Home](#)[^ Top of Page](#)