



Overview

Moveable spotlights for highlighting performers; requires an operator.

A compact, versatile followspot with a choice of light sources to suit throw distances up to 22m/72ft; ideal for schools, small venues and production/rental use.

Accessories, parts and supplies

Find compatible accessories, parts and supplies for this product in the products section.

[Compatible products](#)

Accessories



Pacific Followspot colour changer

[Read on ►](#)



Pacific Followspot Stand

[Read on ►](#)

Beam angle range 7.5°-19°

Performance data
 600W - 1000 lux at 18.5m
 800W - 1000 lux at 20m
 1000W - 1000 lux at 20m
 80V 1200W - 1000 lux at 23m

220V-240V: metric / Lux

Related Models

[Pacific 5° Fixed Beam](#)
[Pacific 12°-28° Zoomspot](#)
[Pacific 14°-35° Zoomspot](#)
[Pacific 20° Fixed Beam](#)
[Pacific 23°-50° Zoomspot](#)
[Pacific 30° Fixed Beam](#)
[Pacific 40° Fixed Beam](#)
[Pacific 45°-75° Zoomspot](#)
[Pacific 5.5°-13° Zoomspot](#)
[Pacific 50° Fixed Beam](#)
[Pacific 7.5°-19° Zoomspot](#)
[Pacific 90° Fixed Beam](#)

Downloads

Product specification sheet PDF

[International](#)
[North America](#)

Operating manual PDF

[International](#)

Bid specification sheet PDF

[International](#)
[North America](#)

Other

[Selecon Warranty](#)
[CE Certificate](#)

| | | Beam Diameter in metres | | | | | | | | | |
|-----------------------|------|-------------------------|-------|-------|------|------|------|------|------|------|------|
| Beam angle | 7.5° | 0 | 0.8 | 1.3 | 2.0 | 2.6 | 3.3 | 3.9 | 4.6 | 5.2 | 5.9 |
| | 19° | 0 | 2.0 | 3.3 | 5.0 | 6.7 | 8.4 | 10.0 | 11.7 | 13.4 | 15.1 |
| Throw Distance metres | | 0 | 6 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 |
| | | | | | | | | | | | |
| Lamp | | Light output in lux | | | | | | | | | |
| 240V GKV 600W | 7.5° | Peak | 9600 | 3456 | 1536 | 864 | 553 | 384 | 282 | 216 | 171 |
| | | Flat | 9600 | 3456 | 1536 | 864 | 553 | 384 | 282 | 216 | 171 |
| | 19° | Peak | 4650 | 1674 | 744 | 419 | 268 | 186 | 137 | 105 | 83 |
| | | Flat | 1750 | 630 | 280 | 158 | 101 | 70 | 51 | 39 | 31 |
| 240V GKV 800W | 7.5° | Peak | 11400 | 4104 | 1824 | 1026 | 657 | 456 | 335 | 257 | 203 |
| | | Flat | 11400 | 4104 | 1824 | 1026 | 657 | 456 | 335 | 257 | 203 |
| | 19° | Peak | 5750 | 2070 | 920 | 518 | 331 | 230 | 169 | 129 | 102 |
| | | Flat | 2760 | 994 | 442 | 248 | 159 | 110 | 81 | 62 | 49 |
| 240V BP 1000W | 7.5° | Peak | 11120 | 4003 | 1779 | 1001 | 641 | 445 | 327 | 250 | 198 |
| | | Flat | 11120 | 4003 | 1779 | 1001 | 641 | 445 | 327 | 250 | 198 |
| | 19° | Peak | 5700 | 2052 | 912 | 513 | 328 | 228 | 168 | 128 | 101 |
| | | Flat | 3050 | 1098 | 488 | 275 | 176 | 122 | 90 | 69 | 54 |
| 80V 1200W | 7.5° | Peak | 15420 | 5551 | 2467 | 1388 | 888 | 617 | 453 | 347 | 274 |
| | | Flat | 15420 | 5551 | 2467 | 1388 | 888 | 617 | 453 | 347 | 274 |
| | 19° | Peak | 8050 | 2898 | 1288 | 725 | 464 | 322 | 237 | 181 | 143 |
| | | Flat | 6000 | 2160 | 960 | 540 | 346 | 240 | 176 | 135 | 107 |
| MSR 575 / 2 | 7.5° | Peak | 51500 | 18540 | 8240 | 4635 | 2966 | 2060 | 1513 | 1159 | 916 |
| | | Flat | 51500 | 18540 | 8240 | 4635 | 2966 | 2060 | 1513 | 1159 | 916 |
| | 19° | Peak | 19700 | 7092 | 3152 | 1773 | 1135 | 788 | 579 | 443 | 350 |
| | | Flat | 7500 | 2700 | 1200 | 675 | 432 | 300 | 220 | 169 | 133 |
| MSR 575W HR | 7.5° | Peak | 42100 | 15156 | 6736 | 3789 | 2425 | 1684 | 1237 | 947 | 748 |
| | | Flat | 42100 | 15156 | 6736 | 3789 | 2425 | 1684 | 1237 | 947 | 748 |
| | 19° | Peak | 17700 | 6372 | 2832 | 1593 | 1020 | 708 | 520 | 398 | 315 |
| | | Flat | 7500 | 2700 | 1200 | 675 | 432 | 300 | 220 | 169 | 133 |

120V: imperial / FootCandles

| | | Beam Diameter in feet | | | | | | | | | |
|---------------------|------|-----------------------------|------|------|------|------|------|------|-------|------|-------|
| Beam angle | 7.5° | 0 | 2.6 | 4.3 | 6.4 | 8.6 | 10.7 | 12.9 | 15.0 | 17.2 | 19.3 |
| | 19° | 0 | 6.6 | 11.0 | 16.4 | 22.0 | 27.4 | 32.9 | 38.4 | 43.8 | 49.4 |
| Throw Distance feet | | 0 | 19.7 | 32.8 | 49 | 65.6 | 82 | 98.4 | 114.8 | 131 | 147.6 |
| | | | | | | | | | | | |
| Lamp | | Light output in footcandles | | | | | | | | | |
| 115V 575W GLC | 7.5° | Peak | 1206 | 435 | 195 | 109 | 70 | 48 | 36 | 27 | 21 |
| | | Flat | 1206 | 435 | 195 | 109 | 70 | 48 | 36 | 27 | 21 |
| | 19° | Peak | 544 | 196 | 88 | 49 | 31 | 22 | 16 | 12 | 10 |
| | | Flat | 256 | 92 | 41 | 23 | 15 | 10 | 8 | 6 | 5 |
| 115V 750W | 7.5° | Peak | 1283 | 463 | 207 | 116 | 74 | 51 | 38 | 29 | 23 |
| | | Flat | 1283 | 463 | 207 | 116 | 74 | 51 | 38 | 29 | 23 |
| | 19° | Peak | 635 | 229 | 103 | 57 | 37 | 25 | 19 | 14 | 11 |
| | | Flat | 287 | 104 | 46 | 26 | 17 | 12 | 8 | 6 | 5 |
| 115V BP 1000W | 7.5° | Peak | 1241 | 448 | 201 | 112 | 72 | 50 | 37 | 28 | 22 |
| | | Flat | 1241 | 448 | 201 | 112 | 72 | 50 | 37 | 28 | 22 |
| | 19° | Peak | 648 | 234 | 105 | 58 | 37 | 26 | 19 | 15 | 12 |
| | | Flat | 352 | 127 | 57 | 32 | 20 | 14 | 10 | 8 | 6 |
| MSR 575 / 2 | 7.5° | Peak | 4769 | 1720 | 771 | 430 | 275 | 191 | 140 | 108 | 85 |
| | | Flat | 4769 | 1720 | 771 | 430 | 275 | 191 | 140 | 108 | 85 |
| | 19° | Peak | 1824 | 658 | 295 | 164 | 105 | 73 | 54 | 41 | 32 |
| | | Flat | 694 | 250 | 112 | 63 | 40 | 28 | 20 | 16 | 12 |
| MSR 575W HR | 7.5° | Peak | 3898 | 1406 | 630 | 352 | 225 | 156 | 115 | 88 | 69 |
| | | Flat | 3898 | 1406 | 630 | 352 | 225 | 156 | 115 | 88 | 69 |
| | 19° | Peak | 1639 | 591 | 265 | 148 | 95 | 66 | 48 | 37 | 29 |
| | | Flat | 694 | 250 | 112 | 63 | 40 | 28 | 20 | 16 | 1 |

Accessories adjustable, braced fold-down stand, 4-colour changer

Pattern size A

| | |
|------------------------------|----------------------------------|
| Luminaire weight | 19.25kg 42lb 7oz |
| Stand weight | 5.9kg 13lb |
| Colour changer weight | 3.8kg 8lb 7oz |
| Certification | Compliant to CE. ETL pending. |

Recommended Lamps

| 220-240V | 115V |
|---|---|
| 600W GKV 400hrs average life | 575W GLC 400hrs average life |
| 600W GLB 1500hrs average life | 575W GLA 1500hrs average life |
| 800W 400hrs average life | 750W 400hrs average life |
| 1000W GAD 250hrs average life | 1000W GAC 250hrs average life |
| 1000W GAB 250hrs average life | 575W MSR575HR 750hrs average life |
| 80V 1200W 300hrs average life | 575W MSR575/2 700hrs average life |
| 575W MSR575HR 750hrs average life | 575W MSD 575 3000hrs average life |
| 575W MSR575/2 700hrs average life | |
| 575W MSD 575 3000hrs average life | |